

DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

Revision: 6a
Date: 04/15/1991

WASHINGTON, D. C.

M A S T E R M I N I M U M E Q U I P M E N T L I S T

CESSNA 425/441

Aircraft Evaluation Group, ACE-270
Department of Transportation
Federal Aviation Administration
Central Region - Federal Building
601 East 12th Street
Kansas City, Missouri 64106

Telephone: (816) 426-3946

FTS: 867-3946

CESSNA 425/441

Table of Contents

SYSTEM NO.	SYSTEM	PAGE
--	Table of Contents	I
--	Log of Revisions	II
--	Control Page	III, IV
--	Highlights of Change	V
--	Definitions	VI, VII, VIII, IX
--	Definitions	X, XI
--	Preamble	XII, XIII
--	Guidelines for (O) & (M) Procedures	XIV, XV
21	Air Conditioning	21-1, 2, 3, 4, 5
22	Auto Flight	22-1
23	Communications	23-1
25	Equipment/Furnishings	25-1, 2
25	Equipment/Furnishings	25-1, 2
26	Fire Protection	26-1
27	Flight Controls	27-1
28	Fuel	28-1
29	Hydraulic Power	29-1
30	Ice and Rain Protection	30-1
31	Indicating/Recording Systems	31-1
32	Landing Gear	32-1
33	Lights	33-1, 2
34	Navigation	34-1, 2, 3
35	Oxygen	35-1
52	Doors	52-1
61	Propellers	61-1
76	Engine Controls	76-1
77	Engine Indicating	77-1
79	Engine Oil	79-1

CESSNA 425/441

Log of Revisions

REV.NO.	DATE	PAGE NUMBERS	INITIALS
ORIGINAL			
1	12/23/1982		
2	12/5/1984	Pen & Ink Changes to Page 21-2	
3	3/5/1987	76-1	
4	6/1/1989	ALL PAGES	
5	6/22/1989	PREAMBLE	
6	3/25/1991	HIGHLIGHTS OF REV., DEFINITIONS	
6	3/25/1991	GUIDELINES	
6	3/25/1991	21-1, 21-2, 21-3, 21-4, 21-5	
6	3/25/1991	22-1, 23-1, 25-1, 26-1, 27-1	
6	3/25/1991	28-1, 29-1, 30-1, 31-1, 32-1	
6	3/25/1991	33-1, 33-2, 34-1, 34-2, 35-1	
6	3/25/1991	61-1	
6a	4/15/1991	HIGHLIGHTS OF REV.	
6a	4/15/1991	23-1	

CESSNA 425/441

Control Page

SYSTEM	PAGE	REV NO.	CURRENT DATE
Cover Page	-	6	04/15/1991
Table of Contents	I	6a	4/15/1991
Log of Revisions	II	6a	4/15/1991
Control Page	III	6a	4/15/1991
	IV	6a	4/15/1991
Highlights of Change	V	6a	4/15/1991
Definitions	VI	3	10/2/1989
	VII	3	10/2/1989
	VIII	3	10/2/1989
	IX	3	10/2/1989
	X	3	10/2/1989
	XI	3	10/2/1989
Preamble	XII	2	6/14/1989
	XIII	2	6/14/1989
Guidelines for (O) & (M) Procedures	XIV	6	3/25/1991
	XV	6	3/25/1991
21	21-1	6	3/25/1991
	21-2	6	3/25/1991
	21-3	6	3/25/1991
	21-4	6	3/25/1991
	21-5	6	3/25/1991
22	22-1	6	3/25/1991
23	23-1	6a	4/15/1991
25	25-1	6	3/25/1991
	25-2	4	6/1/1989
26	26-1	6	3/25/1991
27	27-1	6	3/25/1991
28	28-1	6	3/25/1991
29	29-1	6	3/25/1991
30	30-1	6	3/25/1991
31	31-1	6	3/25/1991
32	32-1	6	3/25/1991
33	33-1	6	3/25/1991
	33-2	6	3/25/1991
34	34-1	6	3/25/1991
	34-2	6	3/25/1991
	34-3	4	6/1/1989
35	35-1	6	3/25/1991
52	52-1	4	6/1/1989
61	61-1	6	3/25/1991

CESSNA 425/441

Control Page

SYSTEM	PAGE	REV NO.	CURRENT DATE
76	76-1	4	6/1/1989
77	77-1	4	6/1/1989
79	79-1	4	6/1/1989

CESSNA 425/441

Highlights of Change

1. This revision adds relief for Cockpit Voice Recorders.

CESSNA 425/441

Definitions

(Effective 10/2/89)

1. System Definitions.

System numbers are based on the Air Transport Association (ATA) Specification Number 100 and items are numbered sequentially.

- a. "Item" (Column 1) means the equipment, system, component, or function listed in the "Item" column.
- b. "Number Installed" (Column 2) is the number (quantity) of items normally installed in the aircraft. This number represents the aircraft configuration considered in developing this MMEL. Should the number be a variable (e.g., passenger cabin items) a number is not required.

NOTE: Where the MMEL shows a variable number installed, the MEL must reflect the actual number installed or an alternate means of configuration control approved by the Administrator.

- c. "Number Required for Dispatch" (Column 3) is the minimum number (quantity) of items required for operation provided the conditions specified in Column 4 are met.

NOTE: Where the MMEL shows a variable number required for dispatch, the MEL must reflect the actual number required for dispatch or an alternate means of configuration control approved by the Administrator.

- d. "Remarks or Exceptions" (Column 4) in this column includes a statement either prohibiting or permitting operation with a specific number of items inoperative, provisos (conditions and limitations) for such operation, and appropriate notes.
- e. A vertical bar (change bar) in the margin indicates a change, addition or deletion in the adjacent text for the current revision of that page only. The change bar is dropped at the next revision of that page.

2. "Airplane/Rotorcraft Flight Manual" (AFM/RFM) is the document required for type certification and approved by the responsible FAA Aircraft Certification Office. The FAA approved AFM/RFM for the specific aircraft is listed on the applicable Type Certificate Data Sheet.

CESSNA 425/441

Definitions

(Effective 10/2/89)

3. "As required by FAR" means that the listed item is subject to certain provisions (restrictive or permissive) expressed in the Federal Aviation Regulations operating rules. The number of items required by the FAR must be operative. Items installed that are in excess of the FAR requirements may be permitted by the operator's MEL to be inoperative if not otherwise required by the MMEL.

4. "*" symbol in Column 4 indicates the listed item if inoperative, must be placarded to inform and remind the crewmembers and maintenance personnel of the equipment condition.

NOTE: To the extent practical, placards should be located adjacent to the control or indicator for the item affected; however, unless otherwise specified, placard wording and location will be determined by the operator.

5. "-" symbol in Column 2 and/or Column 3 indicates a variable number (quantity) of the item installed.

NOTE: Where the MMEL shows a variable number installed, the MEL must reflect the actual number installed or an alternate means of configuration control approved by the Administrator.

6. "Deleted" in the remarks column after a sequence item indicates that the item was previously listed but is now required to be operative if installed in the aircraft.

7. "ER" refers to extended range operations of a two-engine airplane which has a type design approval for ER operations and complies with the provisions of Advisory Circular 120-42A.

CESSNA 425/441

Definitions

(Effective 10/2/89)

8. "Federal Aviation Regulations" (FAR) means the applicable portions of the Federal Aviation Act and Federal Aviation Regulations.
9. "Flight Day" means a 24 hour period (from midnight to midnight) either Universal Coordinated Time (UCT) or local time, as established by the operator, during which at least one flight is initiated for the affected aircraft.
10. "Icing Conditions" means an atmospheric environment that may cause ice to form on the aircraft or in the engine(s).
11. Alphabetical symbol in Column 4 indicates a proviso (condition or limitation) that must be complied with for operation with the listed item inoperative.
12. "Inoperative" means a system and/or component malfunction to the extent that it does not accomplish its intended purpose and/or is not consistently functioning normally within its approved operating limit(s) or tolerance(s).
13. "Notes:" in Column 4 provides additional information for crewmember or maintenance consideration. Notes are used to identify applicable material which is intended to assist with compliance, but do not relieve the operator of the responsibility for compliance with all applicable requirements. Notes are not a part of the provisos.
14. Inoperative components of an inoperative system: Inoperative items which are components of a system which is inoperative are usually considered components directly associated with and having no other function than to support that system. (Warning/caution systems associated with the inoperative system must be operative unless relief is specifically authorized per the MMEL).

CESSNA 425/441

Definitions

(Effective 10/2/89)

15. "(M)" symbol indicates a requirement for a specific maintenance procedure which must be accomplished prior to operation with the listed item inoperative. Normally these procedures are accomplished by maintenance personnel; however, other personnel may be qualified and authorized to perform certain functions. Procedures requiring specialized knowledge or skill, or requiring the use of tools or test equipment should be accomplished by maintenance personnel. The satisfactory accomplishment of all maintenance procedures, regardless of who performs them, is the responsibility of the operator. Appropriate procedures are required to be published as part of the operator's manual or MEL.

16. "(O)" symbol indicates a requirement for a specific operations procedure which must be accomplished in planning for and/or operating with the listed item inoperative. Normally these procedures are accomplished by the flight crew; however, other personnel may be qualified and authorized to perform certain functions. The satisfactory accomplishment of all procedures, regardless of who performs them, is the responsibility of the operator. Appropriate procedures are required to be published as a part of the operator's manual or MEL.

NOTE: The (M) and (O) symbols are required in the operator's MEL unless otherwise authorized by the Administrator.

17. "Deactivated" and "Secured" means that the specified component must be put into an acceptable condition for safe flight. An acceptable method of securing or deactivating will be established by the operator.

18. "Visual Flight Rules" (VFR) is as defined in FAR Part 91. This precludes a pilot from filing an Instrument Flight Rules (IFR) flight plan.

19. "Visual Meteorological Conditions" (VMC) means the atmospheric environment is such that would allow a flight to proceed under the visual flight rules applicable to the flight. This does not preclude operating under Instrument Flight Rules.

CESSNA 425/441

Definitions

(Effective 10/2/89)

20. "Visible Moisture" means an atmospheric environment containing water in any form that can be seen in natural or artificial light; for example, clouds, fog, rain, sleet, hail, or snow.

21. "Passenger Convenience Items" means those items related to passenger convenience, comfort or entertainment such as, but not limited to, galley equipment, movie equipment, ash trays, stereo equipment, overhead reading lamps, etc.

22. Repair Intervals: All users of an MEL approved under FAR 121, 125, 129 and 135 must effect repairs of inoperative systems or components, deferred in accordance with the MEL, at or prior to the repair times established by the following letter designators:

Category A. Items in this category shall be repaired within the time interval specified in the remarks column of the operator's approved MEL.

Category B. Items in this category shall be repaired within three (3) consecutive calendar days (72 hours), excluding the day the malfunction was recorded in the aircraft maintenance record/logbook. For example, if it were recorded at 10 a.m. on January 26th, the three day interval would begin at midnight the 26th and end at midnight the 29th.

Category C. Items in this category shall be repaired within ten (10) consecutive calendar days (240 hours), excluding the day the malfunction was recorded in the aircraft maintenance record/logbook. For example, if it were recorded at 10 a.m. on January 26th, the 10 day interval would begin at midnight the 26th and end at midnight February 5th.

The letter designators are inserted adjacent to Column 2.

23. Engine Indicating Crew Alerting System (EICAS), Electronic Centralized Aircraft Monitoring System (ECAM) or similar systems that provide electronic messages refer to a system capable of providing different priority levels of systems information messages (e.g., Warning, Caution, Advisory Status and Maintenance). Any airplane discrepancy message that affects dispatchability will normally be at status message level (e.g., Advisory Status) or higher.

CESSNA 425/441

Definitions

(Effective 10/02/89)

24. "Administrative control item" means an item listed by the operator in the MEL for tracking and informational purposes. It may be added to an operator's MEL by approval of the Principal Operations Inspector provided no relief is granted, or provided conditions and limitations are contained in an approved document (i.e. Structural Repair Manual, airworthiness directive, etc.). If relief other than that granted by an approved document is sought for an administrative control item, a request must be submitted to the Administrator. If the request results in review and approval by the FOEB, the item becomes an MMEL item rather than an administrative control item.

25. "****" symbol in Column 1 indicates an item which is not required by regulation but which may have been installed on some models of aircraft covered by this MMEL. This item may be included on the operator's MEL after the approving office has determined that the item is installed on one or more of the operator's aircraft. The symbol, however, shall not be carried forward into the operator's MEL. It should be noted that neither this definition nor the use of this symbol provide authority to install or remove an item from an aircraft.

CESSNA 425/441

Preamble
(Effective 6/14/89)

The following is applicable for authorized certificate holders operating under Federal Aviation Regulations (FAR) Parts 121, 125, 129, 135: The FAR require that all equipment installed on an aircraft in compliance with the Airworthiness Standards and the Operating Rules must be operative. However, the Rules also permit the publication of a Minimum Equipment List (MEL) where compliance with certain equipment requirements is not necessary in the interests of safety under all operating conditions. Experience has shown that with the various levels of redundancy designed into aircraft, operation of every system or installed component may not be necessary when the remaining operative equipment can provide an acceptable level of safety. A Master Minimum Equipment List (MMEL) is developed by the FAA, with participation by the aviation industry, to improve aircraft utilization and thereby provide more convenient and economic air transportation for the public. The FAA approved MMEL includes those items of equipment related to airworthiness and operating regulations and other items of equipment which the Administrator finds may be inoperative and yet maintain an acceptable level of safety by appropriate conditions and limitations; it does not contain obviously required items such as wings, flaps, and rudders. The MMEL is the basis for development of individual operator MELs which take into consideration the operator's particular aircraft equipment configuration and operational conditions. Operator MELs, for administrative control, may include items not contained in the MMEL; however, relief for administrative control items must be approved by the Administrator. An operator's MEL may differ in format from the MMEL, but cannot be less restrictive than the MMEL. The individual operator's MEL, when approved and authorized, permits operation of the aircraft with inoperative equipment.

Equipment not required by the operation being conducted and equipment in excess of FAR requirements are included in the MEL with appropriate conditions and limitations. The MEL must not deviate from the Aircraft Flight Manual Limitations, Emergency Procedures or with Airworthiness Directives. It is important to remember that all equipment related to the airworthiness and the operating regulations of the aircraft not listed on the MMEL must be operative.

CESSNA 425/441

Preamble
(Effective 6/14/89)

Suitable conditions and limitations in the form of placards, maintenance procedures, crew operating procedures and other restrictions as necessary are specified in the MEL to ensure that an acceptable level of safety is maintained.

The MEL is intended to permit operation with inoperative items of equipment for a period of time until repairs can be accomplished. It is important that repairs be accomplished at the earliest opportunity. In order to maintain an acceptable level of safety and reliability the MMEL establishes limitations on the duration of and conditions for operation with inoperative equipment. The MEL provides for release of the aircraft for flight with inoperative equipment. When an item of equipment is discovered to be inoperative, it is reported by making an entry in the Aircraft Maintenance Record/Logbook as prescribed by FAR. The item is then either repaired or may be deferred per the MEL or other approved means acceptable to the Administrator prior to further operation. MEL conditions and limitations, do not relieve the operator from determining that the aircraft is in condition for safe operation with items of equipment inoperative.

When these requirements are met, an Airworthiness Release, Aircraft Maintenance Record/Logbook entry, or other approved documentation is issued as prescribed by FAR. Such documentation is required prior to operation with any item of equipment inoperative.

Operators are responsible for exercising the necessary operational control to ensure that an acceptable level of safety is maintained. When operating with multiple inoperative items, the interrelationships between those items and the effect on aircraft operation and crew workload will be considered.

Operators are to establish a controlled and sound repair program including the parts, personnel, facilities, procedures, and schedules to ensure timely repair.

WHEN USING THE MEL, COMPLIANCE WITH THE STATED INTENT OF THE PREAMBLE, DEFINITIONS, AND THE CONDITIONS AND LIMITATIONS SPECIFIED IN THE MEL IS REQUIRED.

CESSNA 425/441

Guidelines for (O) & (M) Procedures

The FOEB has identified a need for certain procedures to provide an adequate level of safety while providing relief for the following items. These procedures must be established by the operator. The following guidelines are to help establish these required procedures.

441 ONLY

- 21.1 (M) Procedure to assure no mechanical/electrical faults that could create an unsafe condition.
- 21.2 (M) Procedure to assure no mechanical/electrical faults that could create an unsafe condition.
- 21.3. (M) Procedure to assure valve/valves are in closed position.
- 21.5 (M) Procedure to assure valve is in closed position.
- 21.16 (M) Procedure to assure flow control valves are in closed position.

425 ONLY

- 21.1 (M) Procedure to assure no mechanical/electrical faults that could create an unsafe condition.
- 21.10 (M) Procedure to assure no mechanical/electrical faults that could create an unsafe condition.

425 & 441

- 22.1 (M) Procedure to assure no mechanical/electrical faults that could create an unsafe condition.
- 22.2 (M) Procedure to assure no mechanical/electrical faults that could create an unsafe condition.
- 23.3 (O) Procedure to specify how passengers will be briefed and to operate within the MMEL restrictions.

CESSNA 425/441

Guidelines for (O) & (M) Procedures

- 27.1 (M) Procedure to assure failure of electric trim will not interfere with operation of manual trim.
- 29.1 (M) Procedure to assure that hydraulic pump failure will not adversely affect engine operation or cause contamination or failure of the hydraulic system.
- 31.2 (O) Procedure to record elapsed flight time.
- 32.1 (O) Procedure to prevent movement of aircraft when stopped or parked.
- 33.8 (O) Procedure to appropriately brief passengers.

AIRCRAFT:

CESSNA 425/441

REVISION NO: 6

DATE: 3/25/1991

PAGE:

21-1

SYSTEM & SEQUENCE NUMBERS		Item	1.	2.	NUMBER INSTALLED	3.	NUMBER REQUIRED FOR DISPATCH	4.	REMARKS OR EXCEPTIONS
441 ONLY									
21 AIR CONDITIONING									
1.	Air Cycle Machine	C	1	0					*(M)May be inoperative for unpressurized flight.
2.	Air Conditioner System - Freon	C	1	0					*(M)
3.	Flow Control Valve	C	2	1					*(M)One valve may be inoperative for pressurized flight provided the failed valve is in the closed position.
									OR
		C	2	0					*(M)Both valves may be inoperative in the closed position for unpressurized flight.
4.	Emergency Pressurization Valve	C	1	0					*May be inoperative for unpressurized flight.
5.	Ground Flow Control Valve	C	2	0					*(M)May be inoperative in the closed position.
6.	Cabin Vent Control	C	1	0					*May be inoperative in the open position for unpressurized flight.
7.	Cabin Pressurization Control System	C	1	0					*May be inoperative for unpressurized flight.

AIRCRAFT:

CESSNA 425/441

REVISION NO: 6

DATE: 3/25/1991

PAGE:

21-2

SYSTEM & SEQUENCE NUMBERS		Item	1.	2.	NUMBER INSTALLED	3.	NUMBER REQUIRED FOR DISPATCH	4.	REMARKS OR EXCEPTIONS
441 ONLY									
21 AIR CONDITIONING									
8.	Pressurization Source Selector Switch	C	1	0					*May be inoperative for unpressurized flight with selector switch in OFF position.
9.	Cabin Vertical Speed Indicator	C	1	0					*May be inoperative provided:
									a) Cabin altimeter is operative, and
									b) Differential pressure indicator is operative.
									OR
		C	1	0					*May be inoperative for unpressurized flight.
10.	Cabin Altimeter	C	1	0					*May be inoperative provided cabin differential pressure indicator is operative.
									OR
		C	1	0					*May be inoperative for unpressurized flight.
11.	Cabin Differential Pressure Indicator	C	1	0					*May be inoperative provided cabin altimeter is operative.
									OR
		C	1	0					*May be inoperative for unpressurized flight.

AIRCRAFT:

CESSNA 425/441

REVISION NO: 6

DATE: 3/25/1991

PAGE:

21-3

SYSTEM & SEQUENCE NUMBERS	Item 1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
441 ONLY 21 AIR CONDITIONING		1	0	*May be inoperative for unpressurized flight.
12. Cabin Altitude Warning System	C	1	0	OR *May be inoperative for pressurized flight at or below 10,000 ft. msl.
13. Automatic Cabin Air Temperature Controller	C	1	0	*May be inoperative provided manual control system is operative.
14. Ground Bleed Air Light	C	1	0	*
15. Emergency Pressurization Light				Deleted, Rev. 6
16. Air Duct Overheat Light	C	1	0	*(M)May be inoperative provided: a) Flight is made unpressurized, and b) Pressurized source valves are in the closed position.
17. Cabin Fan	C	1	0	*

AIRCRAFT:

CESSNA 425/441

REVISION NO: 6

DATE: 3/25/1991

PAGE:

21-4

SYSTEM & SEQUENCE NUMBERS		Item	1.	2.	NUMBER INSTALLED	3.	NUMBER REQUIRED FOR DISPATCH	4.	REMARKS OR EXCEPTIONS
425 ONLY									
21 AIR CONDITIONING									
1.	Air Conditioner System	C	1	0					*(M)
2.	Cabin Vent Control	C	1	0					*May be inoperative in the open position for unpressurized flight.
3.	Cabin Pressurization Control System	C	1	0					*May be inoperative for unpressurized flight.
4.	Pressurization Source Selector	C	1	0					*May be inoperative for unpressurized flight with the selector switch in the OFF position.
5.	Cabin Vertical Speed Indicator	C	1	0					*May be inoperative provided:
									a) Cabin altimeter is operative, and
									b) Differential pressure indicator is operative.
									OR
		C	1	0					*May be inoperative for unpressurized flight.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

CESSNA 425/441

REVISION NO: 6

DATE: 3/25/1991

PAGE:

21-5

SYSTEM & SEQUENCE NUMBERS		Item	1.	2.	NUMBER INSTALLED	3.	NUMBER REQUIRED FOR DISPATCH	4.	REMARKS OR EXCEPTIONS
425 ONLY									
21 AIR CONDITIONING									
6.	Cabin Altimeter	C	1	0					*May be inoperative provided differential pressure indicator is operative.
									OR
		C	1	0					*May be inoperative for unpressurized flight.
7.	Cabin Differential Pressure Indicator	C	1	0					*May be inoperative provided cabin altimeter is operative.
									OR
		C	1	0					*May be inoperative for unpressurized flight.
8.	Cabin Altitude Warning System	C	1	0					*May be inoperative for unpressurized flight.
									OR
		C	1	0					*May be inoperative for pressurized flight at or below 10,000 ft. msl.
9.	Cabin Fan	C	1	0					*May be inoperative provided the auxiliary electrical heat is not used.
10.	Auxiliary Electric Heater	C	1	0					*(M)

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

CESSNA 425/441

REVISION NO: 6

DATE: 3/25/1991

PAGE:

22-1

SYSTEM & SEQUENCE NUMBERS		Item	1.	2.	NUMBER INSTALLED	3.	NUMBER REQUIRED FOR DISPATCH	4.	REMARKS OR EXCEPTIONS
22	AUTO FLIGHT								
1.	Autopilot	C	1	0					*(M)As required by FARs.
2.	Yaw Damper	C	1	0					*(M)

AIRCRAFT:

CESSNA 425/441

REVISION NO: 6a

DATE: 4/15/1991

PAGE:

23-1

SYSTEM & SEQUENCE NUMBERS	Item 1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
23 COMMUNICATIONS				
1. Communications Equipment (VHF, HF, UHF)	C	- -		*As required by FARs.
2. Cockpit Voice Recorder (CVR) System	A	1 0		*May be inoperative provided repairs are made within three flight days.
3. Passenger Address	A	1 0		*(O)May be inoperative provided: a) Alternate normal and emergency procedures and/or operating restrictions are established and utilized, b) Appropriate oral briefings are given to passengers, and c) The aircraft may continue the flight or series of flights for a maximum of 15 hours.

AIRCRAFT:

CESSNA 425/441

REVISION NO: 6

DATE: 3/25/1991

PAGE:

25-1

SYSTEM & SEQUENCE NUMBERS	Item 1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
25 EQUIPMENT/FURNISHINGS				
1. Cockpit Shoulder Harness				Deleted, Rev. 6
2. Passenger Seats	C	-	0	<p>*All may be inoperative provided:</p> <p>a) Affected seat does not block emergency egress to the aisle or exit, and</p> <p>b) Affected seat is blocked and placarded "DO NOT OCCUPY."</p> <p>NOTE:</p> <p>1. A seat with an inoperative seat belt or shoulder harness is considered to be inoperative.</p> <p>2. A seat with an inoperative recline mechanism is considered to be inoperative if the seat back cannot be secured in the upright position.</p>
3. Flotation Devices				Deleted, Rev. 6
4. ELT	C	1	0	*As required by FAR
				OR
	C	1	0	<p>*May be inoperative for published scheduled flights in scheduled air carrier service.</p>

AIRCRAFT:

CESSNA 425/441

REVISION NO: 4

DATE: 6/1/1989

PAGE:

25-2

SYSTEM & SEQUENCE NUMBERS	Item 1.	2. NUMBER INSTALLED		3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
25 EQUIPMENT/FURNISHINGS 5. Passenger Convenience Items		-	-		

4. REMARKS OR EXCEPTIONS

*Passenger convenience items, as expressed in this MMEL, are those related to passenger convenience, comfort or entertainment such as but not limited to, galley equipment, movie equipment, ash trays, stereo equipment, overhead reading lamps, etc. Items addressed elsewhere in this document shall not be included. (M) and (0) procedures may be required in the air carrier's appropriate document.

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

REVISION NO: 6

PAGE :

26-1

SYSTEM & SEQUENCE NUMBERS	Item	1.	2.	NUMBER INSTALLED	3.	NUMBER REQUIRED FOR DISPATCH	4.	REMARKS OR EXCEPTIONS
26 FIRE PROTECTION								
1. Portable Fire Extinguisher								Deleted, Rev. 6
2. Fire Extinguishing Systems								Deleted, Rev. 6
3. Total Cabin Flood Fire Extinguishing System	C	1	0	*				

AIRCRAFT:

CESSNA 425/441

REVISION NO: 6

DATE: 3/25/1991

PAGE:

27-1

SYSTEM & Item 1.
SEQUENCE
NUMBERS

2. NUMBER INSTALLED

3. NUMBER REQUIRED FOR DISPATCH

4. REMARKS OR EXCEPTIONS

27 FLIGHT CONTROLS

1. Electric Elevator
Trim System

C

1

0

*(M)

AIRCRAFT:

CESSNA 425/441

REVISION NO: 6

DATE: 3/25/1991

PAGE:

28-1

SYSTEM & SEQUENCE NUMBERS		Item 1.	2. NUMBER INSTALLED		3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
28	FUEL SYSTEM					
1.	Fuel Low Level Warning Lights	C	2	0	*	
2.	Fuel Totalizer	C	1	0	*	

AIRCRAFT:

CESSNA 425/441

REVISION NO: 6

DATE: 3/25/1991

PAGE:

29-1

SYSTEM & SEQUENCE NUMBERS	Item 1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
29 HYDRAULIC POWER				
1. Engine Driven Pumps	C	2	1	*(M)One may be inoperative.
2. Hydraulic Flow Low Lights	C	2	1	*One hydraulic flow low light may be inoperative if the corresponding hydraulic pump is inoperative.

AIRCRAFT:

CESSNA 425/441

REVISION NO: 6

DATE: 3/25/1991

PAGE:

30-1

SYSTEM & SEQUENCE NUMBERS		Item 1.	2. NUMBER INSTALLED		3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
30	ICE AND RAIN PROTECTION					
1.	Pitot Heater	B	2	0		*Left Pitot Heater must be operative for IFR passenger carrying and for flight in known or forecast icing conditions. Two heated pitot tubes are required for these conditions if a second airspeed indicator is installed and operative.
2.	Air Foil De-Ice System	C	1	0		*May be inoperative provided flight is not operated in known or forecast icing conditions.
3.	Heated Windshield System	C	1	0		*May be inoperative provided flight is not operated in known or forecast icing conditions.
4.	Propeller De-Icing Systems	C	2	0		*May be inoperative provided flight is not operated in known or forecast icing conditions.
5.	Stall Warning/ Angle of Attack Heater	C	1	0		*May be inoperative provided flight is not operated in known or forecast icing conditions.
6.	Windshield Alcohol System	C	1	0		*May be inoperative provided flight is not operated in known or forecast icing conditions.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

CESSNA 425/441

REVISION NO: 6

DATE: 3/25/1991

PAGE:

31-1

SYSTEM & SEQUENCE NUMBERS		Item	1.	2. NUMBER INSTALLED		3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
31 INDICATING/RECORDING SYSTEMS							
1.	Clock with sweep second hand, or electric digital readout clock	C	1	0			*May be inoperative for VFR.
2.	Flight Hour Recorder	C	1	0			*(O)
3.	Flight Data Recorder	B	1	0			*May be inoperative provided Cockpit Voice Recorder (CVR) is operative.

AIRCRAFT:

CESSNA 425/441

REVISION NO: 6

DATE: 3/25/1991

PAGE:

32-1

SYSTEM & SEQUENCE NUMBERS		Item 1.	2. NUMBER INSTALLED		3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
32	LANDING GEAR					
1.	Parking Brake	C	1	0		*(O)

AIRCRAFT:

CESSNA 425/441

REVISION NO: 6

DATE: 3/25/1991

PAGE:

33-1

SYSTEM & SEQUENCE NUMBERS		Item	1.	2.	NUMBER INSTALLED	3.	NUMBER REQUIRED FOR DISPATCH	4.	REMARKS OR EXCEPTIONS
33 LIGHTS									
1.	Position Lights	C	3	0					*May be inoperative for day operations.
2.	Anti-collision Beacon Light System	B	1	0					*May be inoperative for day operations.
3.	Landing Lights	C	2	0					*May be inoperative for day operations.
4.	Cockpit and Instrument light System	B	-	-					*May be inoperative provided: <ul style="list-style-type: none"> a) Sufficient lighting is operative to make each required instrument, control and other device for which it is provided, easily readable, b) Direct rays and reflections do not impair visibility either inside or outside the aircraft, c) Lighting intensity can be controlled or preset to a satisfactory level for the expected conditions, and d) Lighting configuration at dispatch is acceptable to the flight crew.
5.	Wing Ice Light		2	0					*May be inoperative provided a portable lamp/light of adequate capacity for wing and/or control surface inspection is available for night operations in icing conditions.
6.	Taxi Light	C	1	0					*

AIRCRAFT:

CESSNA 425/441

REVISION NO: 6

DATE: 3/25/1991

PAGE:

33-2

SYSTEM & SEQUENCE NUMBERS	Item	1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
33 LIGHTS					
7. Wing Tip Recognition lights	C	1	0	*	
8. Passenger Notice (No Smoking - Fasten Seat Belt)	C	1	0		*(O)May be inoperative provided appropriate verbal briefings are given to passengers.
9. Oxygen Light					Deleted, Revision 6 (Item moved to page 35-1)

AIRCRAFT:

CESSNA 425/441

REVISION NO: 6

DATE: 3/25/1991

PAGE:

34-1

SYSTEM & SEQUENCE NUMBERS		Item	1.	2.	NUMBER INSTALLED	3.	NUMBER REQUIRED FOR DISPATCH	4.	REMARKS OR EXCEPTIONS
34	NAVIGATION								
1.	Altimeters, Adjustable for barometric pressure	B	2	1					*May be inoperative on right side for day VMC. NOTE: Where a servoed electric altimeter is installed, a functioning pneumatic indicator is required.
2.	Airspeed	C	2	1					*May be inoperative on right side for day VMC. NOTE: Where a servoed electric airspeed is installed, a functioning pneumatic indicator is required.
3.	Gyroscopic Pitch and Bank Indicator Systems	B	2	1					*May be inoperative on right side for day VMC.
4.	Gyroscopic Rate of Turn/Slip Skid Indicators	B	2	1					*Must be operative on left side for IFR, passenger carrying VFR over the top, and passenger carrying VFR night flights.
5.	Gyroscopic Directional Indicator Systems	B	2	1					*May be inoperative on right side for day VMC.
6.	Vertical Speed Indicators	B	2	0					*Must be operative on left side for IFR passenger carrying operations.
7.	Transponder	C	1	-					*As required by FAR.
8.	Navigation Equipment (VOR/ILS, Loran, Omega/VLF, GPS INS, Doppler, RNAV)	C	-	-					*As required by FAR.

AIRCRAFT:

CESSNA 425/441

REVISION NO: 6

DATE: 3/25/1991

PAGE:

34-2

SYSTEM & SEQUENCE NUMBERS	Item 1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
34 NAVIGATION				
9. Weather Radar/ Thunderstorm Detection Equipment	C	1	0	*As required by FAR.
10. Marker Beacon	C	1	0	*May be inoperative provided approach procedure does not require its use.
11. Flight Director	C	1	0	*
12. Radio Altimeter	C	1	0	*
13. Altitude Encoder	C	1	0	*As required by FAR.
14. DME	C	1	0	*As required by FAR.
15. Standby Attitude Indicator	C	1	0	*May be inoperative for day VFR.
16. ADF	C	1	0	*As required by FAR.
17. RMI	C	1	0	*
18. Altitude Alert	B	1	0	*
19. Angle of Attack System	C	1	0	*

AIRCRAFT:

CESSNA 425/441

REVISION NO: 4

DATE: 6/1/1989

PAGE:

34-3

SYSTEM & SEQUENCE NUMBERS	Item 1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
34 NAVIGATION 20. Nonstabilized Magnetic Compass	B	1	0	*May be inoperative provided any combination of three gyro or INS (IRU) stabilized compass systems are operative.
	B	1	0	<p style="text-align: center;">OR</p> <p>*May be inoperative provided:</p> <p>a) Any combination of two gyro or INS stabilized compass systems are operative, and</p> <p>b) Aircraft is operated with dual independent navigation capability and under positive radar control by ATC on the enroute portion of the flight.</p>
	B	1	0	<p style="text-align: center;">OR</p> <p>*May be inoperative for flights that are entirely within areas of magnetic unreliability provided at least two stabilized directional gyro systems are installed, operative, and used in conjunction with approved free gyro navigation techniques.</p>

AIRCRAFT:

CESSNA 425/441

REVISION NO: 6

DATE: 3/25/1991

PAGE:

35-1

SYSTEM & Item 1.
SEQUENCE
NUMBERS

2. NUMBER INSTALLED

3. NUMBER REQUIRED FOR DISPATCH

4. REMARKS OR EXCEPTIONS

35 OXYGEN

1. Oxygen System
(Passengers)

C

-

-

*As required by FARs.

2. Oxygen Light

C

1

0

*

AIRCRAFT:

CESSNA 425/441

REVISION NO: 4

DATE: 6/1/1989

PAGE:

52-1

SYSTEM & SEQUENCE NUMBERS	Item 1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
52 DOORS 1. Door Seal	C	1	0	*May be inoperative for unpressurized flight.

U.S. DEPARTMENT OF TRANSPORTATION

MASTER MINIMUM EQUIPMENT LIST

FEDERAL AVIATION ADMINISTRATION

AIRCRAFT:

CESSNA 425/441

REVISION NO: 6

DATE: 3/25/1991

PAGE:

61-1

SYSTEM & SEQUENCE NUMBERS		Item 1.	2. NUMBER INSTALLED		3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
61	PROPELLERS					
1.	Propeller	C	1	0	*	
	Synchronizer					
	Synchrophaser					

AIRCRAFT:

CESSNA 425/441

REVISION NO: 4

DATE: 6/1/1989

PAGE:

76-1

SYSTEM & SEQUENCE NUMBERS	Item 1.	2. NUMBER INSTALLED	3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
76 ENGINE CONTROLS 1. Electronic Fuel Computer (Cessna 441)	C	2	0	<p>*May be inoperative provided:</p> <p>a) Manual mode operating procedures in AFM are followed,</p> <p>b) Manual mode performance charts in AFM are used, and</p> <p>c) Propeller reversing is not permitted for the engine operating in manual mode.</p> <p>NOTE:</p> <p>Propeller synchrophaser is inoperative in manual mode.</p>

AIRCRAFT:

CESSNA 425/441

REVISION NO: 4

DATE: 6/1/1989

PAGE:

77-1

SYSTEM & SEQUENCE NUMBERS		Item 1.	2. NUMBER INSTALLED		3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
77	ENGINE INDICATING					
1.	Fuel Flow Indicators	C	2	0		*Both may be inoperative.

AIRCRAFT:

CESSNA 425/441

REVISION NO: 4

DATE: 6/1/1989

PAGE:

79-1

SYSTEM & SEQUENCE NUMBERS		Item 1.	2. NUMBER INSTALLED		3. NUMBER REQUIRED FOR DISPATCH	4. REMARKS OR EXCEPTIONS
79	ENGINE OIL					
2.	Oil Cooler Flap Control System (425)	C	2	0		*May be inoperative in the trail or fully open position provided the oil temperature is closely monitored.